Best Practices for Chiller Systems for Performance Enhancement of Combustion Turbines During Hot Weather

By Trey Sims

Sponsored by:

Turbine Inlet Cooling Association (TICA) October 8, 2014; 1 PM (U.S. Central Time) https://members.meetingzone.com/presenter/default.aspx Call-In Number: 1 877 406 7969 Access Code: 2603587#



INTRODUCTIONS





Dharam Punwani

- President
 - Avalon Consulting, Inc.
- Executive Director, TICA



Trey Sims

- Turnkey Sales Manager
- TAS Energy





Who is TICA?

- The Turbine Inlet Cooling Association (TICA) promotes the development and exchange of knowledge related to gas turbine inlet cooling
- The TICA website is one-stop source of TIC technical information, including Installation Database & Performance Calculator
- TICA is a non-profit organization.



TICA Member Benefits

- Access to full/detailed version of TIC Installation Database
- Access to full/detailed version of the TIC Technology Performance Calculator
- GT Users get access to the TIC Forum
- Suppliers information is included in the Resource Guide on TICA Website, have access to advertisement space on that site, and have opportunity to display literature at the TICA booths at various electric power trade shows



Become a Member Today!!! Turbine Inlet Cooling Best Practices Upcoming Webinar Schedule

December 12, 2014: Thermal Energy Storage

February 11, 2015: Wet Compression

April 8, 2015: Hybrid Systems



All Webinars start at 1 PM (U.S. Central Time)

AGENDA

TAS Introduction

- Technology Overview Generation Storage & Inlet Chilling
- Project Examples
- Best Practices
- Questions



COMPANY INTRODUCTION



CORE COMPETENCIES

TURBINE INLET CO

turbineinletcooling.org

© 2012 TAS Energy. All Rights Reserved.

MANUFACTURING FACILITY

- Houston, TX HQ
- 275,000 sq ft
- 80 Ton Crane Capacity
- In-house pneumatic tes
 - Pressure & Leak Testing





© 2012 TAS Energy. All Rights Reserved.

Technology Overview



Turbine Inlet Chilling (TIC) & Generation Storage (GS)

- Gas turbines only operate at 100% of their rated capacity when the temperature outside is 59F.
- As temperatures climb into the 90's and beyond, greater than 10% of the capacity of the turbine disappears.
- By chilling below rated capacity and adding storligest power is recovered, and additional power is generated.
- Storage and ancillary services including ramping benefits are captured as well



WATER-COOLED MECHANICAL



GS: More Than Just Capacity



Generation Storage - PFD





PFD-CHARGE 12/10/2



PFD – PARTIAL DISCHARGE 12/10/2



PFD – FULL DISCHARGE 12/10/2



F-SKID FEATURES



F-SKID FEATURES



© 2012 TAS Energy. All Rights Reserved.

TES TANK CONSTRUCTION

einletcooling.org

TURR

© 2012 TAS Energy. All Rights Reserved.

TES TANK CONSTRUCTION

Pre-Stressing Calibrated Wire Spacing

© 2012 TAS Energy. All Rights Reserved.

TES TANK INTERNALS

Lower Diffuser Manifold

© 2012 TAS Energy. All Rights Reserved.

TYPICAL LAYOUT

TURBINE INLET COOLING ASSOCIATION turbineinletcooling.org

© 2012 TAS Energy. All Rights Reserved.

Texas Cooperative

- GE 7FA in CC (2 Blocks of 2x1) •
- Two (2) F Packaged Chiller Systems
- One Thermal Energy Storage Tank
- Start-Up in 2010 (retrofit) & 2012 (new plant)

Project Timing: 2008-2009 Outage Duration: ~15-30 Days Construction Man-Hours: ~50,000 Construction Duration: ~9 Months Project Timing: 2008-2009

© 2012 TAS Energy. All **Rights Reserved.**

Texas Cooperative

- Siemens 501FC in CC (1x1)
- One (1) Packaged Chiller Systems
- One Thermal Energy Storage Tank 1.74 M gallons
- Start-Up in 2012

© 2012 TAS Energy. All Rights Reserved.

24

Retofit

Duke Power – Buck CC Plant

- GE 7FA in CC (2x1)
- Two (2) F Packaged Chiller Systems
- COD in 2011

TES Tank

Duke Power – Dan River CC Plant

- GE 7FA in CC (2x1)
- Two (2) F Packaged Chiller Systems
- COD in 2012

© 2012 TAS Energy. All Rights Reserved.

Dominion – Fairless Energy

- GE 7FA in CC (2 blocks of 2x1)
- 2 TAS Packaged Chiller Systems
- 1 Thermal Energy Storage Tank
- Completed in 2008
- Filter House Retrofit for Inlet Coils

TANK SIZE: 7.6 MG POWER INCREASE: 115 MW

Near Trenton, NJ

© 2012 TAS Energy. All Rights Reserved.

Dominion – Bear Garden

- GE 7FA Combined Cycle Plant (2x1)
- 1 TAS Packaged Chiller Systems
- 1 Thermal Energy Storage Tank
- Completed in 2011

TANK SIZE: 3.9 MG POWER INCREASE: 60 MW

© 2012 TAS Energy. All Rights Reserved.

Dominion – Warren County

- MHI 501G Combined Cycle Plant (3x1)
- 3 TAS Packaged Chiller Systems
- 1 Thermal Energy Storage Tank
- Start-Up in 2014

© 2012 TAS Energy. All Rights Reserved.

Dominion – Brunswick County

- MHI 501G Combined Cycle Plant (3x1)
- 4 TAS Packaged Chiller Systems
- 1 Thermal Energy Storage Tank
- Start-Up in 2016

TANK SIZE: 10.7 MG POWER INCREASE: 123 MW EPC: Fluor

© 2012 TAS Energy. All Rights Reserved.

Turbine Inlet Chilling (TIC) Generation Storage

Best Practices

DESIGNING THE SYSTEM

WHAT IS THE DRIVER FOR ADDITIONAL CAPACITY?

- Do you need the added capacity 24 hours per day
- How many hours do you want highest output
- What are revenue considerations
 - How valuable is another 5-7 MW on top of system addition
- Will there be an expansion effort onsite in future
- Availability of water
 TURBINE INLET COOLING ASSOCIATION furbineinletcooling.org
 © 2012 T. Rights Re

© 2012 TAS Energy. All Rights Reserved.

AF COIL MODULE DESIGN

© 2012 TAS Energy. All Rights Reserved.

CONCENTRIC VS. ECCENTRIC

BEFORE

- Eccentric Inlet Duct
- Extended Inlet Duct for Fogging

AFTER

- Concentric Inlet Duct
- New Spacer Elevates Inlet Duct
- Existing Filter House Utilized

© 2012 TAS Energy. All Rights Reserved.

BEST PRACTICTES

WINTERIZATION

- No Glycol
- Drainable coils
- Not required on the TES

COIL CONDENSATE

- Good quality
- Water makeup flexibility

© 2012 TAS Energy. All Rights Reserved.

SERIES COUNTERFLOW: EFFICIENCY

Lower Parasitic Loads

Higher CHW delta T = smaller TES tank, Pumps

BEST PRACTICTES

SUPER PEAK – 12/10/2 (charge, partial discharge, SuperPeak)

- Max benefit, lowest parasitics
- Larger Secondary Pump Skid, TES Tank flow rate

DESIGN CONDITION

- Design condition (95°F drybulb, 75°F wetbulb)
- 24 hour design DAY

BEST PRACTICTES

TES TANK

- AWWA Standard D-110, Type III
- Water Tight
- Thermal performance
- Concrete lower life cycle cost, no painting

© 2012 TAS Energy. All Rights Reserved.

Thank You!

Trey Sims tsims@tas.com 281.229.4469

